

	Question	Code Reference
1	Maximum floor area of one-story detached accessory structure	Section R105.2, #B1
2	Sprinklered owner-occupied lodging houses permitted under IRC	Section R101.2, Exc. 2
3	Notice of a code violation	Section R113.2
4	fire-resistance rating for exterior walls with automatic sprinkler system	Sec. R302.1, Table R302.1(2)
5	Door between garage and residence	Section R302.5.1
6	Max. clear height of uninhabitable attic areas with 10 psf live load	Table 301.5, Note b
7	Wall assembly separating two dwelling units does not extend through the attic space	Section R302.3, Exc. 2
8	Ladder or steps for window well serving an escape and rescue opening	Section R310.2.3.1
9	Glazing within an arc of a door	Section R308.4.2
10	Minimum height of walls finished with a nonabsorbent surface in shower	Section R307.2
11	Minimum headroom in a stairway, including at landings	Section R311.7.2
12	Applicability of Group R-3 accessibility provisions from IBC Chapter 11	Section R320.1
13	Min. clearance between foam plastics in very heavy termite infestation	Section R318.4
14	Min. 3/4-inch nosing is required at treads unless min. tread depth exists	Section R311.7.5.3, Exc.
15	Min. opening in floor to provide access to under-floor space	Section R408.4
16	Top of exterior foundation wall height above street gutter	Section R403.1.7.3
17	Backfill against foundation wall with wall anchored to the floor	Section R404.1.7, Exc.
18	Underside of floor assemblies	Section 302.13
19	Lag screws in deck ledger supported by attachment	Table R507.2.1, Figure R507.2.1(1)
20	Concrete slab-on-ground	Section R506.1
21	Max. allowable header span	Table R602.7(1)
22	Double top plates lapped at corners and intersections require fasteners	Table R602.3(1), Item 17
23	Class A, B or C roofing installed unless	Section R902.1
24	Taper cut at the end of a ceiling joist	Section R802.7.1.2
25	Wood roof shingles laid with min. side lap	Section R905.7.5
26	Exposed combustible trim on masonry fireplace front	Section R1001.11, Exc. 4
27	Metal rain cap net free area	Section R1003.9.3
28	Min. 3/8-inch-thick noncombustible hearth extension permitted where bottom of firebox opening above hearth extension	Section R1001.9.2, Exc.
29	Thickness of insulation written on markers installed in attic space	Section N1101.10.1.1
30	Passageway max. length for access to an appliance in underfloor space	Section M1305.1.4, Exc. 2
31	Solid-fuel-burning appliance min. clearance	Section M1306.2.3
32	Secondary drain piping for refrigeration cooling equipment	Section M1411.3.1
33	Clothes dryer exhaust ducts support	Section M1502.4.2

Exc. = exception

	Question	Code Reference
34	Outdoor air inlets screens for return air system	Section R303.6
35	Airflow for continuous whole-house mechanical ventilation system	Table M1507.3.3(1)
36	Polybutylene (PB) hydronic piping installed in concrete	Table M2101.1
37	Fuel oil tanks installed above ground	Section M2201.2.2
38	Gas-fired unvented room heater	Section G2406.2, #3
39	Minimum required duration of a pressure test for gas piping	Section G2417.4.2
40	Supports for 3/4-inch steel gas pipe	Table G2424.1
41	Extension of unthreaded portion of gas piping outlets	Section G2415.16
42	Rigid support sway bracing for plumbing pipe at bends	Section P2605.1, #3
43	Curb height for shower receptor	Section P2709.1
44	Laundry tray outlet distance from standpipe trap	Section P2706.1.2.1
45	Attic sprinklers intermediate temperature rating	Section P2904.2.2
46	Deck-mounted vacuum breakers installed above flood level rim	Section P2902.4.2
47	Connection between vent pipe and vent stack	Section P3104.5
48	Min. required clearance in front of a cleanout	Section P3005.2.9
49	Subsoil drains for storm drainage	Section P3302.1
50	Min. required trap size for floor drain	Table P3201.7
51	Max. slope of vent section of horizontal branch drain in circuit venting	Section P3110.3
52	Min. work space dimensions of electrical panelboard	Section E3405.2
53	Overhead service conductors min. clearance on roofs	Section E3604.2.1, Exc. 5
54	Min. length of free conductor for electrical conductors	Section E3406.11.3
55	Foyers receptacles	Section E3901.11
56	Recessed fluorescent luminaire in storage closet	Section E4003.12, #4
57	Min. receptacle distance from walls of indoor spas and hot tubs	Section E4203.1.4
58	Material of ducts penetrating walls separating dwelling from garage	Section R302.5.2
59	Min. gypsum board under stairs	Section R302.7
60	Max. smoke-developed index for wall and ceiling finishes	Section R302.9.2
61	Laundry rooms min. ceiling height	Section R305.1
62	Mesh openings of screens below skylights	Section R308.6.7
63	Provisions of IBC Chapter 11 apply	Section R320.1
64	Installation of smoke alarms near bathrooms	Section R314.3, #4
65	Concrete footing width and thickness	Table R403.1(2)
66	Max. height of retaining wall resisting additional lateral loads	Section R404.4

Exc. = exception

	Question	Code Reference
67	Pressure preservative-treated wood basement floors	Section R504.1.1
68	Max. joist spacing for wood decking applied diagonally to joists	Section R507.4
69	Steel splice plate required as alternative for single wood top plate	Table R602.3.2
70	Screw attachment for corner framing of Structural Insulated Panels (SIPS)	Section R610.9, Fig. R610.9
71	Truss uplift force from wind	Table R802.11
72	Photovoltaic shingles permitted on roofs	Section R605.16.2
73	Hearth extension required for a masonry fireplace	Section R1001.10
74	Exterior air outlet required for a factory-built or masonry fireplace	Section R1006.5
75	Shield plates to protect mechanical systems piping in framing member	Section M1308.2.3
76	Mechanical system equipment supported on a concrete slab	Section M1305.1.4.1
77	Clothes dryer exhaust duct size	Section M1502.4.1
78	Markings on mastics used to seal metallic and flexible air ducts	Section M1601.4.1
79	Type L venting systems	Section M1804.2.4
80	Heat-pump ground-loop system solder joint	Section M2105.10.2
81	Field-drilled or tapped gas pipe fittings	Section G2414.10.4, #5.1
82	Shower liner test	Section P2503.6
83	Hub drains	Section P2706.1.1
84	Sump pit serving a building subdrain	Section P3007.3.2
85	Distribution piping for a subsurface landscape irrigation system	Section P3009.11
86	Roughed-in drainage piping for future fixtures	Section P3104.6
87	Trap size for shower with multiple showerheads and body sprays	Table P3201.7
88	Metal water piping used as a conductor in the ground electrode system	Section E3611.4
89	Ranges supplied by a branch circuit	Section E3702.9.1
90	Flexible cord for a cord-and-plug-connected in-sink waste disposer	Table E4101.3
91	Luminaires in outdoor pool areas	Section E4203.4.1

Exc. = exception